



PROVIDENCE PIPE PRODUCTS

1465 Tamarind Ave #229 Los Angeles, CA 90048
 P: (562) 803-1273 F: (562) 803-0376

Features:

- Low conductivity, high corrosion resistance
- Defect free interior and exterior

Applications:

- Allows direction changes in EMT conduit.

Material:


- Hot dip galvanized steel

Standards:

- UL797
- NEMA: ANSI C80.3



Rigid Elbow 90° - HDG



Specifications and Packaging Chart

Size	Unit Carton	Ship Case	Weight Case	(A) Min. UL Radius	(B) Straight Leg Each End	(C)Offset
1/2"	---	50	40	4	2.875	6.343
3/4"	---	50	54	4.5	2.875	6.781
1"	---	20	40	5.75	3	8.901
1-1/4"	---	20	60	7.25	3.25	10.25
1-1/2"	---	10	42	8.25	3.625	11.937
2"	---	10	68	9.5	4.1875	14.031
2-1/2"	1	50	650	10.5	5.25	16
3"	1	35	630	13	5.8125	18.947
3-1/2"	1	35	910	15	6.75	22.218
4"	1	25	825	16	6.9375	23.437
5"	1	30	1350	24	11.125	36.156
6"	1	24	1152	30	12.4375	41.46



PROVIDENCE PIPE PRODUCTS

1465 Tamarind Ave #229 Los Angeles, CA 90048

P: (562) 803-1273 F: (562) 803-0376

Features:

- Low conductivity, high corrosion resistance
- Defect free interior and exterior

Applications:

- Allows direction changes in EMT conduit.


Material:

- Hot dip galvanized steel

Standards:

- UL797
- NEMA: ANSI C80.3

Rigid Elbow 45° - HDG



Specifications and Packaging Chart

Size	Unit Carton	Ship Case	Weight Case	(A) Min. UL Radius	(B) Straight Leg Each End
1/2"	---	50	26	4	2.875
3/4"	---	50	38	4.5	2.875
1"	---	35	45	5.75	3
1-1/4"	---	30	60	7.25	3.25
1-1/2"	---	15	45	8.25	3.625
2"	---	15	68	9.5	4.1875
2-1/2"	1	50	400	10.5	5.25
3"	1	40	455	13	5.8125
3-1/2"	1	35	560	15	6.75
4"	1	35	770	16	6.9375
5"	1	42	1840	24	8.125
6"	1	36	2556	30	13.25



PROVIDENCE PIPE PRODUCTS

1465 Tamarind Ave #229 Los Angeles, CA 90048

P: (562) 803-1273 F: (562) 803-0376

Features:

- Low conductivity, high corrosion resistance
- Defect free interior and exterior

Applications:

- Allows direction changes in EMT conduit.


Material:

- Hot dip galvanized steel

Standards:

- UL797
- NEMA: ANSI C80.3

Rigid Elbow 22.5° - HDG



Specifications and Packaging Chart

Size	Unit Carton	Ship Case	Weight Case	(A) Min. UL Radius	(B) Straight Leg Each End
1-1/4"	---	20	34	7.25	2.781
1-1/2"	---	15	36	8.25	2.781
2"	---	10	38	9.5	2.781
2-1/2"	1	50	400	10.5	3
3"	1	35	385	13	3.125
3-1/2"	1	35	490	15	3.281
4"	1	35	630	16	3.375